

56H Series (3 hp) Horizontal Grinders

Tools Renewed Inc
800-247-3639 Fax 860-665-9821



56-HL with 6" wheel guard



56-HS with lockout lever throttle and plug wheel adaptor

HEAVY DUTY HORIZONTAL GRINDERS

The 56-H Horizontal Grinder can perform material removal and finishing work quickly and efficiently. It is adaptable for use with 6" or 8" type 1 straight grinding wheels, 9" type 27 wheels, plug wheels, and wire brushes.

3 hp SPECIFICATIONS										
Model	Throttle Type	Speed	Spindle Type	Overall Length	Side to Center Distance	Weight	Rated Power	Inlet Size	Hose Size	Working Air Consumption
56-HL	Lever Throttle	4500 to 8000 rpm (6000 rpm is standard)	5/8-11 x 1.75" 44mm	21.2" 533mm	1.41" 31mm	101 lb.	3 H.P. 2.25 Kw	1/2" N.P.T.	1/2"	45 cfm
56-HS	Lockout Lever Throttle					4.8 kg				
56-HG	Spade Grip Handle					103/4 lb. 4.9 kg				

Features:

- Corrosion resistant stainless steel governor keeps the tool at a steady R.P.M. while maintaining maximum power.
- Heavy-duty double row bearings provide maximum spindle support.
- Common motor parts with 65-V Series reduces spare parts inventory.
- Front seal in bearing cap keeps dirt from entering bearings.
- Choice of (1) 6", 8" type 1 wheel guard. 9" type 27 wheel guard or plug wheel adaptor.
- Choice of lever, lock-out lever or spade grip throttle.

All Henry Air Tools® are manufactured in the U.S.A. and comply with O.S.H.A. standards.

65H Series (4 hp) Horizontal Grinders



65-HL with 8" wheel guard



65-HS with lockout lever throttle and plug wheel adaptor

HEAVY DUTY HORIZONTAL GRINDERS

The 65-H Horizontal Grinder is one of the most powerful grinders manufactured. This tool is designed for heavy metal removal and finishing operations on welds, castings, forgings, or any metal construction. It is adaptable for use with 6" or 8" type 1 straight grinding wheels, 9" type 27 wheels, plug wheels, and wire brushes.

4 hp SPECIFICATIONS										
Model	Throttle Type	Speed	Spindle Type	Overall Length	Side to Center Distance	Weight	Rated Power	Inlet Size	Hose Size	Working Air Consumption
65-HL	Lever Throttle	4000 to 8000 rpm (6000 rpm is standard)	5/8-11 x 1.75" 44mm	23.6 599mm	1-1/4" 31mm	12-1/2 lb. 5.67 kg	4 H.P. 3.0 Kw	1/2" N.P.T.	1/2"	50 cfm
65-HS	Lockout Lever Throttle					12-3/4 lb. 5.8 kg				
65-HG	Spade Grip Handle									

**51H (1-1/2 hp)
Horizontal Grinders**



51-HKS with lockout lever throttle and 4" Wheel Guard



511-HKS with lockout lever throttle and 5/8-11 stub spindle for plug type wheels

HEAVY DUTY SMALL WHEEL HORIZONTAL GRINDERS

This series of small wheel horizontal grinders are lightweight yet rugged tools. These tools are ideal for use with plug wheels, 3" and 4" grinding wheels or collet chuck work.

SPECIFICATIONS									
Model	Throttle Type	Speed	Spindle Type	Net Weight	Overall Length	Air Inlet	Hose Size	Rated Power	Working Air Consumption
51-HLS	Lever	15,000 to 18,000 rpm (specify when ordering)	3/8"-24 or 1/2"-13 x 1" (25mm)	6 1/2 lbs. 2.8 kg	17.8" 431 mm	1/2" N.P.T.	1/2"	1.5 H.P. 1.13 Kw	35 cfm
51-HKS	Lockout Lever								
51-HGS	Spade Grip								
511-HLS	Lever								
511-HKS	Lockout Lever								
511-HGS	Spade Grip								
GOVERNED MODELS									
57-HLS	Lever	7000 to 15,000 rpm (specify when ordering)	3/8"-24 or 1/2"-13 x 1" (25mm)	8.0 3.7 kg	18.5 457mm	1/2" N.P.T.	1/2"	1.5 H.P. 1.13 Kw	35 cfm
57-HKS	Lockout Lever								
57-HGS	Spade Grip								
517-HLS	Lever								
517-HKS	Lockout Lever								
517-HGS	Spade Grip								

**52H (2 hp)
Horizontal Grinders**



52-HSJ with lockout lever throttle and 5/8-11 Stub Spindle for use with cone and plug wheels



52-HG with Spade Handle and 6" Guard

HEAVY DUTY HORIZONTAL GRINDERS

The 52-H Horizontal Grinders provide high power-to-weight ratio in a slim tool. Versatility and power make the 52-H excellent for fast metal removal and tight quarter cleaning jobs. This tool is ideal for use with wire brushes, 4" and 6" type 1 wheel applications, or cone and plug wheels.

SPECIFICATIONS									
Model	Throttle Type	Speed	Net Weight	Overall Length	Spindle Type	Air Inlet	Hose Size	Rated Power	Working Air Consumption
52-HL	Lever	6000, 9000, 12,000 rpm	712 lbs. - 3.4 kg	18-1/4"	5/8-11 x 2 1/4 (57mm)	1/2" N.P.T.	1/2"	2 H.P.	40 cfm
52-HS	Lockout Lever		8 1/8 lbs. - 3.7 kg		5/8-11 x .900"			1.5 Kw	
52-HG	Spade Grip Handle								