

Concrete Scabblers



Thor U-Type Multi-Scabblers

Thor U-Type Scabblers Tools are specifically designed for all types of concrete surface work where it is necessary to carry out surface hammering without in any way causing damage to the basic concrete. Stadium seating, concrete walkways, floors, retaining walls, airport runways, bridges, or similar large areas where it is required to expose the aggregate prior to top coating.

The machines are mounted on wheels for ease of transportation, but while the machines are operating the wheels rise clear of the working surface and the machines virtually float, enabling them to be manipulated with ease in a scything motion. Handle design gives good balance and control, together with conveniently placed "on/off" valve, makes machine operation extremely simple for the operator.



U5 (shown)

THOR U-TYPE MULTI-SCABLERS

| MODEL# | U3 | U5 | U7 | U11 |
|---|-----------------------|---------------------|---------------------|---------------------|
| Overall Length Including Handle | 50" (1270 mm) | 50" (1270 mm) | 50" (1270 mm) | 50" (1270 mm) |
| Working Width Over Bits | 5-5/8" (143 mm) | 11-1/4" (286 mm) | 15-3/4" (400 mm) | 19" (483 mm) |
| Total Width Over Wheels | 17" (432 mm) | 25" (635 mm) | 30" (762 mm) | 33" (833 mm) |
| CFM | 100 | 150 | 200 | 300 |
| Hose Size | 1" (25.4 mm) | 1" (25.4 mm) | 1" (25.4 mm) | 1" (25.4 mm) |
| Weight | 125 lbs (57 kg) | 214 lbs (97 kg) | 266 lbs (121 kg) | 308 lbs (140 kg) |
| Length In. | 50" (1270 mm) | 50" (1270 mm) | 50" (1270 mm) | 50" (1270 mm) |
| Scabbling Rate ft ² /hr x 1/8" deep (m ² /hr x 1/8") | 135'-202' (12.5-19 m) | 225'-338' (21-31 m) | 315'-472' (29-44 m) | 495'-742' (46-69 m) |
| Number of Bits | 3 | 5 | 7 | 11 |

Tools Renewed Inc
 800-247-3639 Fax: 860-665-9821
 Web: www.toolsrenewed.com